



HOLLAND STORES

OILFIELD SUPPLY AND SERVICES GMBH

<u>DUAL DUROMETER BONDED PISTON</u>		PART NO.
 <p>The Holland Stores DUAL DUROMETER BONDED PISTONS are manufactured from specially engineered urethane compounds that provides superior resistance to water, oil and synthetic based drilling fluids. The compound also provides superior resistance to tear, abrasion and is capable of operating in fluid temperatures up to 300°F (150°C). The lower part of Piston is made up of urethane compound which has very good Anti extrusion property which enhances the life of the piston</p> <ul style="list-style-type: none"> * "Bull Nose", design promises ease of assembly when loading into the liner due to the smooth engagement of the piston into the liner bore * Extra strong sealing area increases run times even at pressures up to 7500 psi * Reduced maintenance Reduced operational costs * Specially engineered Urethane compound, provides: high resistance to water, oil and synthetic based drilling fluids * Temperature Resistance up to 300(150°C) * Superior resistance to tear, abrasion and extrusion * Well-designed piston body for strong bonding with urethane and reduced weight * Bonded design prevents fluid migration and abrasion between liner body and Pistons. 	PISTON 4"	HSDD-40K14/15
	PISTON 4.5"	HSDD-44K14/15
	PISTON 5"	HSDD-50B14/15
	PISTON 5.5"	HSDD-54B14/15
	PISTON 6"	HSDD-60B14/15
	PISTON 6.25"	HSDD-62L14/15
	PISTON 6.5"	HSDD-64L14/15
	PISTON 6.75"	HSDD-66L14/15
	PISTON 7"	HSDD-70L14/15

